

Package ‘anabel’

May 11, 2023

Title Analysis of Binding Events + 1

Version 3.0.1

Description A free software for a fast and easy analysis of 1:1 molecular interaction studies.

This package is suitable for a high-throughput data analysis.

Both the online app and the package are completely open source.

You provide a table of sensogram, tell 'anabel' which method to use, and it takes care of all fitting details.

The first two releases of 'anabel' were created and implemented as in (<[doi:10.1177/1177932218821383](https://doi.org/10.1177/1177932218821383)>, <[doi:10.1093/database/baz101](https://doi.org/10.1093/database/baz101)>).

License MIT + file LICENSE

Encoding UTF-8

RoxygenNote 7.2.3

VignetteBuilder knitr

LazyData true

Imports cli (>= 3.4), dplyr (>= 1.0), ggplot2 (>= 3.3), kableExtra (>= 1.3), minpack.lm (>= 1.2), openxlsx (>= 4.2), progress (>= 1.2), purrr (>= 0.3), qpdf, reshape2 (>= 1.4), rlang (>= 1.0), stats (>= 4.0), tidyr (>= 1.2), utils (>= 4.0)

Depends R (>= 4.0)

Suggests htmltools (>= 0.5), knitr (>= 1.36), rmarkdown (>= 2.17), testthat (>= 3.0.0), withr

Config/testthat/edition 3

NeedsCompilation no

Author Hoor Al-Hasani [aut, cre] (<<https://orcid.org/0000-0002-0431-845X>>),
Oliver Selinger [aut] (<<https://orcid.org/0000-0001-9723-2809>>),
Stefan Kraemer [aut] (<<https://orcid.org/0000-0002-0071-9344>>)

Maintainer Hoor Al-Hasani <anabel@biocopy.de>

Repository CRAN

Date/Publication 2023-05-11 11:50:02 UTC

R topics documented:

| | |
|-----------------------------|---|
| convert_toMolar | 2 |
| MCK_dataset | 3 |
| MCK_dataset_drift | 3 |
| run_abel | 4 |
| SCA_dataset | 6 |
| SCA_dataset_drift | 7 |
| SCK_dataset | 7 |
| SCK_dataset_decay | 8 |

| | |
|--------------|----------|
| Index | 9 |
|--------------|----------|

| | |
|-----------------|--------------------------------|
| convert_toMolar | <i>Convert a unit to molar</i> |
|-----------------|--------------------------------|

Description

convert the value into molar.

Usage

```
convert_toMolar(val, unit)
```

Arguments

| | |
|------|--|
| val | numeric value of the analyte concentration |
| unit | character string indicating the unit from which, the analyte concentration will be converted into molar. |

Details

supported units are: millimolar, micromolar, nanomolar and picomolar. The name of the unit could be written, or its abbreviation such as: nanomolar (nm), micromolar (mim), picomolar (pm), or millimolar (mm). The unite in either form is case insensitive.

Value

The value of analyte concentration in molar

Examples

```
convert_toMolar(120, "nanomolar")
convert_toMolar(120, "nm")
convert_toMolar(120, "millimolar")
convert_toMolar(120, "mm")
convert_toMolar(120, "micromolar")
convert_toMolar(120, "mim")
convert_toMolar(120, "picomolar")
```

```
convert_toMolar(120, "pm")
```

MCK_dataset

Simulated data of binding curve for MCK.

Description

A dataset containing 5 different binding curves of different analyte concentrations. $K_a = 1e+7nM$, $K_d = 1e-2$

Usage

```
data(MCK_dataset)
```

Format

A data frame with 403 rows and 6 variables:

Time time points of the binding interaction from start to end

Conc..50.nM. binding curve generated with analyte concentration = 50nM

Conc..16.7.nM. binding curve generated with analyte concentration = 16.7nM

Conc..5.56.nM. binding curve generated with analyte concentration = 5.56nM

Conc..1.85.nM. binding curve generated with analyte concentration = 1.85nM

Conc..6.17e.1.nM. binding curve generated with analyte concentration = 0.617nM

Source

<https://apps.cytivalifesciences.com/spr/>

MCK_dataset_drift

Simulated data of binding curve for MCK with linear drift.

Description

A dataset containing 5 different binding curves of different analyte concentrations with induced baseline drift = -0.01. $K_a = 1e+7nM$, $K_d = 1e-2$

Usage

```
data(MCK_dataset)
```

Format

A data frame with 403 rows and 6 variables:

Time time points of the binding interaction from start to end

Conc..50.nM. binding curve generated with analyte concentration = 50nM

Conc..16.7.nM. binding curve generated with analyte concentration = 16.7nM

Conc..5.56.nM. binding curve generated with analyte concentration = 5.56nM

Conc..1.85.nM. binding curve generated with analyte concentration = 1.85nM

Conc..6.17e.1.nM. binding curve generated with analyte concentration = 0.617nM

Source

<https://apps.cytivalifesciences.com/spr/>

run_abel

Analysis for 1:1 Biomolecular Interactions

Description

Analysis for 1:1 biomolecular interactions, using one of single-curve analysis (SCA), single-cycle kinetics (SCK) or multi-cycle kinetics (MCK)

Usage

```
run_abel(  
  input = NA,  
  samples_names_file = NULL,  
  tstart = NA,  
  tend = NA,  
  tass = NA,  
  tdiss = NA,  
  conc = NA,  
  drift = FALSE,  
  decay = FALSE,  
  quiet = TRUE,  
  method = "SCA",  
  outdir = NA,  
  generate_output = "none",  
  generate_Report = FALSE,  
  generate_Plots = FALSE,  
  generate_Tables = FALSE,  
  save_tables_as = "xlsx",  
  debug_mode = FALSE  
)
```

Arguments

| | |
|--------------------|---|
| input | Data.frame, an excel, or a csv file (full path) - required |
| samples_names_file | An optional data.frame, an excel, or a csv file (full path) containing the samples names. If provided, it must have two columns, Name and ID. ID: names of columns in the input file; Name: sample's names. |
| tstart | Numeric value of time's starting point (default: minimum time point in the input) |
| tend | Numeric value of time's ending point (default: maximum time point in the input) |
| tass | Numeric value of association time - required |
| tdiss | Numeric value of dissociation time - required |
| conc | Numeric value, the used concentration of the analyte; should be in molar (see convert_toMolar) - required |
| drift | Boolean value, to apply drift correction (default: FALSE) |
| decay | Boolean value, to apply surface decay correction (default: FALSE) |
| quiet | Boolean value, to suppress notifications, messages and warnings (default: TRUE) |
| method | a character string indicating which fitting method to be used. One of "SCA", "SCK", or "MCK", case insensitive (default: SCA). |
| outdir | Path and name of the output directory in which the results will be saved (default: NA) |
| generate_output | a character string indicating what kind of output will be generated. One of "none", "all", or "customized", case insensitive (default: none). If "all" or "customized" were given, outdir is required. If "customized" was given, at least one of generate_Plots, generate_Tables, or/and generate_Report must be set to TRUE |
| generate_Report | Boolean value, should anabel generate a summary report of the experiment? (default: FALSE) |
| generate_Plots | Boolean value, should anabel generate plots? (default: FALSE). generate_output must be set to "customized" |
| generate_Tables | Boolean value, should anabel generate tables? (default: FALSE) |
| save_tables_as | a character string indicating data format to save the tables with; could be "xlsx", "csv", "txt" or "rds", case insensitive, (default: xlsx) |
| debug_mode | Boolean value, anabel will return additional fitting details for each curve and the estimated response (default: FALSE) |

Value

default returned value is a list of two data frames, the kinetics table and the fit value of each time point (fit_raw). If dev_mode was set to TRUE a third data frame will be returned containing the initial value of the parameters and the fitting function.

References

Determination of rate and equilibrium binding constants for macromolecular interactions by surface plasmon resonance. D J O'Shannessy, M Brigham-Burke, K K Sonesson, P Hensley, I Brooks *Analytical biochemistry* 212, 457-468 (1993)

Analyzing a kinetic titration series using affinity biosensors. Robert Karlsson, Phinikoula S Katsamba, Helena Nordin, Ewa Pol, David G Myszka *Analytical Biochemistry* 349, 136–147 (2006)

Anabel: an online tool for the real-time kinetic analysis of binding events. Stefan D Krämer, Johannes Wöhrle, Christin Rath, Günter Roth *Bioinformatics and Biology Insights* 13, 1-10 (2019)

See Also

[convert_toMolar](#)

Examples

```
# To analyse data using MCK method:
run_anabel(
  input = MCK_dataset, tstart = 1, tass = 21, tdiss = 140,
  conc = c(3.9E-9, 1.6E-8, 6.2E-8, 2.5E-7, 1.0e-6), method = "MCK"
)
```

SCA_dataset

Simulated data for SCA method.

Description

A simulated data containing interaction information of three binding curves all generated with concentration 5e-08,

Usage

```
data(SCA_dataset)
```

Format

A data frame with 453 rows and four variables:

Time time points of the binding interaction from start till the experiment's end

Sample.A sample one with $K_a = 1e+7nM$, $K_d = 1e-2$

Sample.B sample two with $K_a = 1e+6nM$, $K_d = 5e-2$

Sample.C sample four with $K_a = 1e+6nM$, $K_d = 1e-3$

Source

<https://apps.cytivalifesciences.com/spr/>

| | |
|-------------------|---|
| SCA_dataset_drift | <i>Simulated data for SCA method with linear drift.</i> |
|-------------------|---|

Description

A simulated data containing interaction information of three binding curves all generated with concentration $5e-08$, baseline drift = -0.019

Usage

```
data(SCA_dataset)
```

Format

A data frame with 453 rows and four variables:

Time time points of the binding interaction from start till the experiment's end

Sample.A sample one with $K_a = 1e+7nM$, $K_d = 1e-2$

Sample.B sample two with $K_a = 1e+6nM$, $K_d = 5e-2$

Sample.C sample four with $K_a = 1e+6nM$, $K_d = 1e-3$

Source

<https://apps.cytivalifesciences.com/spr/>

| | |
|-------------|---|
| SCK_dataset | <i>Simulated data of different binding curves for SCK method.</i> |
|-------------|---|

Description

A dataset contains one binding curve with 5 titrations-series (5 injection-series), as follows: tass: 50, 220, 390, 560, 730; tdiss: 150, 320, 490, 660, 830; conc: $6.17e-10$ $1.85e-09$ $5.56e-09$ $1.67e-08$ $5.00e-08$ M

Usage

```
data(SCK_dataset)
```

Format

A data frame with 1091 rows and 6 variables:

Time time points of the binding interaction from start to end

Sample.A sample containing 5 titrations with $K_a = 1e+6nM$, $K_d = 1e-2$

Source

<https://apps.cytivalifesciences.com/spr/>

| | |
|-------------------|--|
| SCK_dataset_decay | <i>Simulated data of different binding curves for SCK method with exponential decay.</i> |
|-------------------|--|

Description

A dataset contains one binding curve with 5 titrations-series (5 injection-series), as follows: tass: 50, 220, 390, 560, 730; tdiss: 150, 320, 490, 660, 830; conc: 6.17e-10 1.85e-09 5.56e-09 1.67e-08 5.00e-08 M

Usage

```
data(SCK_dataset)
```

Format

A data frame with 1091 rows and 6 variables:

Time time points of the binding interaction from start to end

Sample.A sample containing 5 titrations with $K_a = 1e+6nM$, $K_d = 1e-2$

Source

<https://apps.cytivalifesciences.com/spr/>

Index

* datasets

MCK_dataset, 3

MCK_dataset_drift, 3

SCA_dataset, 6

SCA_dataset_drift, 7

SCK_dataset, 7

SCK_dataset_decay, 8

convert_toMolar, 2, 5, 6

MCK_dataset, 3

MCK_dataset_drift, 3

run_anabel, 4

SCA_dataset, 6

SCA_dataset_drift, 7

SCK_dataset, 7

SCK_dataset_decay, 8