

Package ‘ib’

October 13, 2022

Type Package

Title Bias Correction via Iterative Bootstrap

Version 0.2.0

Description An implementation of the iterative bootstrap procedure of Kuk (1995) <[doi:10.1111/j.2517-6161.1995.tb02035.x](https://doi.org/10.1111/j.2517-6161.1995.tb02035.x)> to correct the estimation bias of a fitted model object. This procedure has better bias correction properties than the bootstrap bias correction technique.

Maintainer Samuel Orso <Samuel.Orso@unige.ch>

Depends R (>= 4.0.0)

Imports betareg, lme4, Formula, MASS, Matrix, methods, Rdpack (>= 0.7), stats, utils, VGAM

Suggests testthat (>= 3.0.0), knitr, nlraa, rmarkdown

License GPL (>= 2)

Encoding UTF-8

RdMacros Rdpack

RoxygenNote 7.1.2

URL <https://github.com/SMAC-Group/ib/>

BugReports <https://github.com/SMAC-Group/ib/issues/>

Config/testthat/edition 3

NeedsCompilation no

Author Samuel Orso [aut, cre],
Stéphane Guerrier [ctb],
Yuming Zhang [ctb]

Repository CRAN

Date/Publication 2022-04-04 22:50:02 UTC

R topics documented:

bootstrap	2
coef,Ib-method	3
effects,Ib-method	4
fitted,Ib-method	4
getEst	5
getExtra	5
getIteration	6
getObject	7
ib	7
ib,negbin-method	11
IbBetareg-class	12
ibControl	13
plot,Ib,ANY-method	14
predict,Ib-method	15
residuals,Ib-method	15
show,Ib-method	16
show,SummaryIb-method	16
simulation	17
simulation,betareg-method	17
simulation,glm-method	18
simulation,lm-method	18
simulation,lmerMod-method	19
simulation,negbin-method	19
simulation,nls-method	20
simulation,vglm-method	20
summary,IbBetareg-method	21
summary,IbGlm-method	21
summary,IbLm-method	22
summary,IbLmer-method	22
summary,IbNegbin-method	23
summary,IbNls-method	23
summary,IbVglm-method	24
SummaryIbBetareg-class	24
vcov,Ib-method	25
Index	26

bootstrap

*Parametric bootstrap***Description**

Method for generating parametric bootstrap estimates from a fitted model.

Usage

```
bootstrap(object, B = 1000, extra_param = FALSE, ...)
```

Arguments

object an object representing a fitted model (see 'Details').
 B an integer for number of bootstrap replicates (default 1,000).
 extra_param if TRUE, bootstrap is also performed for extra parameters (see 'Details').
 ... additional optional arguments to pass to `ibControl`.

Details

This method is a simple wrapper around the `ib` method where number of iterations is set to 1.

Value

A matrix p (size of parameter) times B of bootstrapped estimates.

Author(s)

Samuel Orso

See Also

[ib](#), [ibControl](#)

coef, Ib-method

Method for extracting coefficients from an object in class union "Ib"

Description

Method for extracting coefficients from an object in class union "Ib"

Usage

```
## S4 method for signature 'Ib'
coef(object, ...)
```

Arguments

object an object of class union "Ib"
 ... further arguments to pass to `coef`

See Also

[Ib](#), [coef](#)

effects,Ib-method *Method for extracting effects from an object in class union "Ib"*

Description

Method for extracting effects from an object in class union "Ib"

Usage

```
## S4 method for signature 'Ib'  
effects(object, ...)
```

Arguments

object	an object of class union "Ib"
...	further arguments to pass to effects

See Also

[Ib, effects](#)

fitted,Ib-method *Method for extracting fitted values from an object in class union "Ib"*

Description

Method for extracting fitted values from an object in class union "Ib"

Usage

```
## S4 method for signature 'Ib'  
fitted(object, ...)
```

Arguments

object	an object of class union "Ib"
...	further arguments to pass to fitted

See Also

[Ib, fitted.values](#)

getEst	<i>Accessor to the object in class union "Ib"</i>
--------	---

Description

Method for obtaining estimates from fitted model within any object of class union [Ib](#).

Usage

```
getEst(x)
```

```
## S4 method for signature 'Ib'  
getEst(x)
```

Arguments

x an object of class union "Ib"

Details

This methods allow to access extra parameter estimates. If extra_param=TRUE, it becomes equivalent to [coef](#).

Value

an estimate (as in [getExtra](#)).

See Also

[Ib](#)

getExtra	<i>Accessor to an extra part in class union "Ib"</i>
----------	--

Description

Method for obtaining a extra values generated by the iterative bootstrap procedure within any object of class union [Ib](#).

Usage

```
getExtra(x)
```

```
## S4 method for signature 'Ib'  
getExtra(x)
```

Arguments

x an object of class union "Ib"

Value

a list with the following components:

iteration	number of iterations (k)
of	value of the objective function $\ \hat{\pi} - \frac{1}{H} \sum_{h=1}^H \hat{\pi}_h(\hat{\theta}^k)\ $
estimate	value of the estimates $\hat{\theta}^k$
test_theta	value for difference of thetas: $\ \hat{\theta}^k - \hat{\theta}^{k-1}\ $
ib_warn	optional warning message
boot	matrix of H bootstrap estimates: $\hat{\pi}(\hat{\theta}^k)$

See Also

[Ib](#)

getIteration	<i>Accessor to the object in class union "Ib"</i>
--------------	---

Description

Method for obtaining the number of iteration from fitted model within any object of class union [Ib](#).

Usage

```
getIteration(x)

## S4 method for signature 'Ib'
getIteration(x)
```

Arguments

x an object of class union "Ib"

Details

This methods allow to access extra information about the number of iterations.

Value

a number of iterations (as in [getExtra](#)).

See Also

[Ib](#)

getObject	<i>Accessor to the object in class union "Ib"</i>
-----------	---

Description

Method for obtaining a fitted model within any object of class union [Ib](#).

Usage

```
getObject(x)

## S4 method for signature 'Ib'
getObject(x)
```

Arguments

x an object of class union "Ib"

See Also

[Ib](#)

ib	<i>Bias correction via iterative bootstrap</i>
----	--

Description

ib is used to correct the bias of a fitted model object with the iterative bootstrap procedure.

Usage

```
ib(object, thetastart = NULL, control = list(...), extra_param = FALSE, ...)

## S4 method for signature 'betareg'
ib(object, thetastart = NULL, control = list(...), extra_param = FALSE, ...)

## S4 method for signature 'glm'
ib(object, thetastart = NULL, control = list(...), extra_param = FALSE, ...)

## S4 method for signature 'lm'
ib(object, thetastart = NULL, control = list(...), extra_param = FALSE, ...)

## S4 method for signature 'lmerMod'
ib(object, thetastart = NULL, control = list(...), extra_param = FALSE, ...)

## S4 method for signature 'nls'
```

```

ib(object, thetastart = NULL, control = list(...), extra_param = FALSE, ...)

## S4 method for signature 'vglm'
ib(object, thetastart = NULL, control = list(...), extra_param = FALSE, ...)

```

Arguments

<code>object</code>	an object representing a fitted model (see 'Details').
<code>thetastart</code>	an optional starting value for the iterative procedure. If <code>NULL</code> (default), the procedure starts at the estimates in <code>object</code> .
<code>control</code>	a list of parameters for controlling the iterative procedure (see <code>ibControl</code>).
<code>extra_param</code>	if <code>TRUE</code> , the bias of estimation of extra parameters is performed (see 'Details').
<code>...</code>	additional optional arguments (see 'Details').

Details

The iterative bootstrap procedure is described in Kuk (1995) and further studied by Guerrier et al. (2019) and Guerrier et al. (2020). The k th iteration of this algorithm is

$$\hat{\theta}^k = \hat{\theta}^{k-1} + \hat{\pi} - \frac{1}{H} \sum_{h=1}^H \hat{\pi}_h(\hat{\theta}^{k-1})$$

for $k = 1, 2, \dots$ and where the sum is over $h = 1, \dots, H$. The estimate $\hat{\pi}$ is provided by the object. The value $\hat{\pi}_h(\hat{\theta})$ is a parametric bootstrap estimate where the bootstrap sample is generated from $\hat{\theta}$ and a fixed seed (see `ibControl`). The greater the parameter value H generally the better bias correction but the more computation it requires (see `ibControl`). If `thetastart=NULL`, the initial value of the procedure is $\hat{\theta}^0 = \hat{\pi}$. The number of iterations are controlled by `maxit` parameter of `ibControl`.

By default, the method correct `coefficients` only. For extra parameters, it depends on the model. These extra parameters may have some constraints (e.g. positivity). If `constraint=TRUE` (see `ibControl`), then a transformation from the constraint space to the real is used for the update.

For `betareg`, `extra_param` is not available as by default mean and precision parameters are corrected. Currently the 'identity' link function is not supported for precision parameters.

For `glm`, if `extra_param=TRUE`: the shape parameter for the `Gamma`, the variance of the residuals in `lm` or the overdispersion parameter of the negative binomial regression in `glm.nb`, are also corrected. Note that the `quasi` families are not supported for the moment as they have no simulation method (see `simulate`). Bias correction for extra parameters of the `inverse.gaussian` is not yet implemented.

For `lm`, if `extra_param=TRUE`: the variance of the residuals is also corrected. Note that using the `ib` is not useful as coefficients are already unbiased, unless one considers different data generating mechanism such as censoring, missing values and outliers (see `ibControl`).

For `lmer`, by default, only the fixed effects are corrected. If `extra_param=TRUE`: all the random effects (variances and correlations) and the variance of the residuals are also corrected. Note that using the `ib` is certainly not useful with the argument `REML=TRUE` in `lmer` as the bias of variance components is already addressed, unless one considers different data generating mechanism such as censoring, missing values and outliers (see `ibControl`).

For `nls`, if `extra_param=TRUE`: the variance of the residuals is also corrected.

For `vglm`, `extra_param` is currently not used. Indeed, the philosophy of a vector generalized linear model is to potentially model all parameters of a distribution with a linear predictor. Hence, what would be considered as an extra parameter in `glm` for instance, may already be captured by the default coefficients. However, correcting the bias of a coefficients does not imply that the bias of the parameter of the distribution is corrected (by **Jensen's inequality**), so we may use this feature in a future version of the package. Note that we currently only support distributions with a `simslot` (see `simulate.vlm`).

Value

A fitted model object of class `lb`.

Author(s)

Samuel Orso

References

Guerrier S, Dupuis-Lozeron E, Ma Y, Victoria-Feser M (2019). "Simulation-Based Bias Correction Methods for Complex Models." *Journal of the American Statistical Association*, **114**(525), 146-157. doi: [10.1080/01621459.2017.1380031](https://doi.org/10.1080/01621459.2017.1380031), <https://doi.org/10.1080/01621459.2017.1380031>.

Guerrier S, Karemera M, Orso S, Victoria-Feser M, Zhang Y (2020). "A General Approach for Simulation-based Bias Correction in High Dimensional Settings." <https://arxiv.org/pdf/2010.13687.pdf>. Version 2: 13 Nov 2020, 2010.13687, <https://arxiv.org/pdf/2010.13687.pdf>.

Kuk AYC (1995). "Asymptotically Unbiased Estimation in Generalized Linear Models with Random Effects." *Journal of the Royal Statistical Society: Series B (Methodological)*, **57**(2), 395-407. doi: [10.1111/j.25176161.1995.tb02035.x](https://doi.org/10.1111/j.25176161.1995.tb02035.x), <https://rss.onlinelibrary.wiley.com/doi/pdf/10.1111/j.2517-6161.1995.tb02035.x>, <https://rss.onlinelibrary.wiley.com/doi/abs/10.1111/j.2517-6161.1995.tb02035.x>.

See Also

[betareg](#)
[glm](#), [glm.nb](#)
[lm](#)
[lmer](#)
[nls](#)
[vglm](#)

Examples

```
## beta regression
library(betareg)
data("GasolineYield", package = "betareg")
```

```
## currently link.phi = "identity" is not supported
## fit_beta <- betareg(yield ~ batch + temp, data = GasolineYield)
fit_beta <- betareg(yield ~ batch + temp, link.phi = "log", data = GasolineYield)
fit_ib <- ib(fit_beta)

# precision parameter can also depend on covariates
fit_beta <- betareg(yield ~ batch + temp | temp, data = GasolineYield)
fit_ib <- ib(fit_beta)
## poisson regression
counts <- c(18,17,15,20,10,20,25,13,12)
outcome <- gl(3,1,9)
treatment <- gl(3,3)
pois_fit <- glm(counts ~ outcome + treatment, family = poisson())
fit_ib <- ib(pois_fit)
summary(fit_ib)
## Set H = 1000
## Not run:
fit_ib <- ib(pois_fit, control=list(H=1000))
summary(fit_ib)

## End(Not run)

## gamma regression
clotting <- data.frame(
  u = c(5,10,15,20,30,40,60,80,100),
  lot1 = c(118,58,42,35,27,25,21,19,18),
  lot2 = c(69,35,26,21,18,16,13,12,12))
fit_gamma <- glm(lot2 ~ log(u), data = clotting, family = Gamma(link = "inverse"))
fit_ib <- ib(fit_gamma)
## summary(fit_ib)
## correct for shape parameter and show iterations
## Not run:
fit_ib <- ib(fit_gamma, control=list(verbose=TRUE), extra_param = TRUE)
summary(fit_ib)

## End(Not run)

## negative binomial regression
library(MASS)
fit_nb <- glm.nb(Days ~ Sex/(Age + Eth*Lrn), data = quine)
fit_ib <- ib(fit_nb)
## summary(fit_ib)
## correct for overdispersion with H=100
## Not run:
fit_ib <- ib(fit_nb, control=list(H=100), extra_param = TRUE)
summary(fit_ib)

## End(Not run)

## linear regression
fit_lm <- lm(displacement ~ cyl + hp + wt, data = mtcars)
fit_ib <- ib(fit_lm)
summary(fit_ib)
```

```

## correct for variance of residuals
fit_ib <- ib(fit_lm, extra_param = TRUE)
summary(fit_ib)

## linear mixed-effects regression
library(lme4)
fit_lmm <- lmer(Reaction ~ Days + (Days | Subject), data = sleepstudy, REML = FALSE)
fit_ib <- ib(fit_lmm)
summary(fit_ib)
## correct for variances and correlation
## Not run:
fit_ib <- ib(fit_lmm, extra_param = TRUE)
summary(fit_ib)

## End(Not run)

## nonlinear regression
DNase1 <- subset(DNase, Run == 1)
fit_nls <- nls(density ~ SSlogis(log(conc), Asym, xmid, scal), data = DNase1)
fit_ib <- ib(fit_nls)
summary(fit_ib)

## student regression
library(VGAM)
tdata <- data.frame(x = runif(nn <- 1000))
tdata <- transform(tdata,
                  y = rt(nn, df = exp(exp(0.5 - x))))
fit_vglm <- vglm(y ~ x, studentt3, data = tdata)
fit_ib <- ib(fit_vglm)
summary(fit_ib)

```

ib,negbin-method [ib](#) method for negbin object from [glm.nb](#) function of **MASS** package.

Description

[ib](#) method for negbin object from [glm.nb](#) function of **MASS** package.

Usage

```

## S4 method for signature 'negbin'
ib(object, thetastart = NULL, control = list(...), extra_param = FALSE, ...)

```

Arguments

object	an object representing a fitted model (see 'Details').
thetastart	an optional starting value for the iterative procedure. If NULL (default), the procedure starts at the estimates in object.
control	a list of parameters for controlling the iterative procedure (see ibControl).

extra_param if TRUE, the bias of estimation of extra parameters is performed (see 'Details').
 ... additional optional arguments (see 'Details').

IbBetareg-class *An S4 class union for ib*

Description

Members of the union are [IbBetareg](#), [IbGlm](#), [IbLm](#), [IbLmer](#), [IbNegbin](#), [IbNls](#), [IbVglm](#)

Details

The 'Functions' section describes members of the class union.

Value

Each member of the union has a slot with the initial object corrected by the `ib` (see [getObject](#)) and a second slot with extra meta data from `ib` (see [getExtra](#)).

Functions

- `IbBetareg-class`: fitted model by `betareg` from **betareg**
- `IbGlm-class`: fitted model by `glm` from **stats**
- `IbLm-class`: fitted model by `lm` from **stats**
- `IbLmer-class`: fitted model by `lmer` from **lme4**
- `IbNegbin-class`: fitted model by `glm.nb` from **MASS**
- `IbNls-class`: fitted model by `nls` from **stats**
- `IbVglm-class`: fitted model by `vglm` from **VGAM**

Author(s)

Samuel Orso

See Also

[getExtra](#), [getObject](#)

 ibControl

Auxiliary for controlling IB

Description

Auxiliary function for `ib` bias correction.

Usage

```

ibControl(
  tol = 1e-05,
  maxit = 25,
  verbose = FALSE,
  seed = 123L,
  H = 1L,
  constraint = TRUE,
  early_stop = FALSE,
  cens = FALSE,
  right = NULL,
  left = NULL,
  mis = FALSE,
  prop = NULL,
  out = FALSE,
  eps = NULL,
  G = NULL,
  func = function(x) rowMeans(x, na.rm = T),
  sim = NULL
)

```

Arguments

<code>tol</code>	positive convergence tolerance ϵ . The <code>ib</code> procedure converges when $\ \hat{\theta}^{k+1} - \hat{\theta}^k\ _2/p < \epsilon$, where p is the dimension of θ .
<code>maxit</code>	integer representing the maximal number of iterations.
<code>verbose</code>	if TRUE, it prints some output in the console at each iteration.
<code>seed</code>	integer to set the seed (see Random).
<code>H</code>	integer representing the number of bootstrap estimates (see <code>ib</code>).
<code>constraint</code>	if TRUE (default), constraint for <code>extra_param</code> is used in the iterative procedure (see 'Details' of <code>ib</code>).
<code>early_stop</code>	if TRUE (default is FALSE), the iterative procedure stops as soon as there is no improvement in the minimization of the objective function (see 'Details' of <code>ib</code>).
<code>cens</code>	if TRUE the simulated responses are censored according to <code>left</code> and <code>right</code> values.
<code>right</code>	double for right-censoring (only used if <code>cens=TRUE</code>).

<code>left</code>	double for left-censoring (only used if <code>cens=TRUE</code>).
<code>mis</code>	if <code>TRUE</code> the simulated responses have missing data at random.
<code>prop</code>	double between 0 and 1 representing the proportion of missing data (only used if <code>mis=TRUE</code>).
<code>out</code>	if <code>TRUE</code> the simulated responses are also generated with a contamination mechanism.
<code>eps</code>	double between 0 and 1 representing the proportion of outliers in the data (only used if <code>out=TRUE</code>).
<code>G</code>	a function to generate outliers. It takes only a sample size as argument.
<code>func</code>	a function to reduce the H bootstrap estimates (rowwise). By default, the average is computed. The user can supply a function. One could imagine using other function such as the median or a trimmed mean.
<code>sim</code>	a user-defined function for simulating responses (see 'Details')

Details

`sim` allows the user to provide its own function for generating responses. Currently it is only supported for generalized linear models with the prototype `'fun(object, control, extra_param, ...)`' (see [ib](#)).

Value

a list with components named as the arguments.

See Also

[ib](#), the iterative procedure for bias correction.

`plot,Ib,ANY-method` *Method for plotting an object in class union "Ib"*

Description

Method for plotting an object in class union "Ib"

Usage

```
## S4 method for signature 'Ib,ANY'
plot(x, y = NULL, ...)
```

Arguments

<code>x</code>	an object of class union "Ib"
<code>y</code>	not used
<code>...</code>	further arguments to pass to <code>plot</code>

See Also[Ib, plot.lm](#)

predict,Ib-method	<i>Method for making predictions from an object in class union "Ib"</i>
-------------------	---

Description

Method for making predictions from an object in class union "Ib"

Usage

```
## S4 method for signature 'Ib'  
predict(object, ...)
```

Arguments

object	an object of class union "Ib"
...	further arguments to pass to predict

See Also[Ib, predict](#)

residuals,Ib-method	<i>Method for extracting residuals from an object in class union "Ib"</i>
---------------------	---

Description

Method for extracting residuals from an object in class union "Ib"

Usage

```
## S4 method for signature 'Ib'  
residuals(object, ...)
```

Arguments

object	an object of class union "Ib"
...	further arguments to pass to residuals

See Also[Ib, residuals](#)

show, Ib-method *Method for printing object in class union "Ib"*

Description

Method for printing object in class union "Ib"

Usage

```
## S4 method for signature 'Ib'  
show(object)
```

Arguments

object an object of class union "Ib"

See Also

[Ib](#)

show, SummaryIb-method *Summarizing a fitted model corrected by the ib procedure*

Description

Method for printing a summary of class union [SummaryIb](#).

Usage

```
## S4 method for signature 'SummaryIb'  
show(object)
```

Arguments

object a summary object of member of [SummaryIb](#)

See Also

[SummaryIb](#)

simulation	<i>Generic for simulating from the object</i>
------------	---

Description

Method for simulating responses from an object.

Usage

```
simulation(object, control = list(...), ...)

## S4 method for signature 'Ib'
simulation(object, control = list(...), ...)
```

Arguments

object	an object of class union "Ib"
control	a control list
...	further argument to pass

Value

simulated responses.

Examples

```
## bootstrap poisson regression
counts <- c(18,17,15,20,10,20,25,13,12)
outcome <- gl(3,1,9)
treatment <- gl(3,3)
pois_fit <- glm(counts ~ outcome + treatment, family = poisson())

## make 100 paramtric bootstrap replicates
boot_dist <- simulate(pois_fit, nsim = 100)
```

simulation, betareg-method	<i>Simulation for a beta regression</i>
----------------------------	---

Description

simulation method for class [IbBetareg](#)

Usage

```
## S4 method for signature 'betareg'
simulation(object, control = list(...), extra = NULL, ...)
```

Arguments

object	an object of class IbBetareg
control	a list of parameters for controlling the iterative procedure (see ibControl).
extra	NULL by default; extra parameters to pass to simulation.
...	further arguments

simulation,glm-method *Simulation for a Generalized Linear Model regression*

Description

simulation method for class [IbGlm](#)

Usage

```
## S4 method for signature 'glm'
simulation(object, control = list(...), extra = NULL, ...)
```

Arguments

object	an object of class IbGlm
control	a list of parameters for controlling the iterative procedure (see ibControl).
extra	NULL by default; extra parameters to pass to simulation.
...	further arguments

simulation,lm-method *Simulation for linear regression*

Description

simulation method for class [IbLm](#)

Usage

```
## S4 method for signature 'lm'
simulation(object, control = list(...), std = NULL, ...)
```

Arguments

object	an object of class IbLm
control	a list of parameters for controlling the iterative procedure (see ibControl).
std	NULL by default; standard deviation to pass to simulation.
...	further arguments

 simulation,lmerMod-method

Simulation for linear mixed model regression

Description

simulation method for class [IbLmer](#)

Usage

```
## S4 method for signature 'lmerMod'
simulation(object, control = list(...), ...)
```

Arguments

object	an object of class IbLmer
control	a list of parameters for controlling the iterative procedure (see ibControl).
...	further arguments.

 simulation,negbin-method

Simulation for a negative binomial regression

Description

simulation method for class [IbNegbin](#)

Usage

```
## S4 method for signature 'negbin'
simulation(object, control = list(...), extra = NULL, ...)
```

Arguments

object	an object of class IbNegbin
control	a list of parameters for controlling the iterative procedure (see ibControl).
extra	NULL by default; extra parameters to pass to simulation.
...	further arguments

simulation, nls-method *Simulation for nonlinear regression*

Description

simulation method for class [IbNls](#)

Usage

```
## S4 method for signature 'nls'
simulation(object, control = list(...), std = NULL, ...)
```

Arguments

object	an object of class IbNls
control	a list of parameters for controlling the iterative procedure (see ibControl).
std	NULL by default; standard deviation to pass to simulation.
...	further arguments

simulation, vglm-method
Simulation for vector generalized linear model regression

Description

simulation method for class [IbVglm](#)

Usage

```
## S4 method for signature 'vglm'
simulation(object, control = list(...), extra_param = NULL, ...)
```

Arguments

object	an object of class IbVglm
control	a list of parameters for controlling the iterative procedure (see ibControl).
extra_param	NULL by default; extra parameters to pass to simulation.
...	further arguments

summary,IbBetareg-method

Summarizing a beta regression fit corrected by the iterative bootstrap

Description

summary method for class [IbBetareg](#)

Usage

```
## S4 method for signature 'IbBetareg'  
summary(object, ...)
```

Arguments

object an object of class [IbBetareg](#)
... further arguments passed to `summary.betareg`

See Also

[summary.betareg](#)

summary,IbGlm-method

Summarizing a Generalized Linear Model regression fit corrected by the iterative bootstrap

Description

summary method for class [IbGlm](#)

Usage

```
## S4 method for signature 'IbGlm'  
summary(object, ...)
```

Arguments

object an object of class [IbGlm](#)
... further arguments passed to `summary.glm`

See Also

[summary.glm](#)

summary,IbLm-method *Summarizing a linear regression fit corrected by the iterative bootstrap*

Description

summary method for class [IbLm](#)

Usage

```
## S4 method for signature 'IbLm'
summary(object, ...)
```

Arguments

object an object of class [IbLm](#)
 ... further arguments passed to `summary.lm`

See Also

[summary.lm](#)

summary,IbLmer-method *Summarizing a linear mixed model regression fit corrected by the iterative bootstrap*

Description

summary method for class [IbLmer](#)

Usage

```
## S4 method for signature 'IbLmer'
summary(object, ...)
```

Arguments

object an object of class [IbLmer](#)
 ... further arguments passed to `summary.merMod` of **lme4**

summary,IbNegbin-method

Summarizing a negative binomial regression fits corrected by the iterative bootstrap

Description

summary method for class [IbNegbin](#)

Usage

```
## S4 method for signature 'IbNegbin'  
summary(object, ...)
```

Arguments

object an object of class [IbNegbin](#)
... further arguments passed to `summary.negbin`

See Also

[summary.negbin](#)

summary,IbNls-method

Summarizing a nonlinear regression fit corrected by the iterative bootstrap

Description

summary method for class [IbNls](#)

Usage

```
## S4 method for signature 'IbNls'  
summary(object, ...)
```

Arguments

object an object of class [IbNls](#)
... further arguments passed to `summary.nls` of **stats**

summary,IbVglm-method *Summarizing a vector generalized linear model regression fit corrected by the iterative bootstrap*

Description

summary method for class [IbVglm](#)

Usage

```
## S4 method for signature 'IbVglm'
summary(object, ...)
```

Arguments

object an object of class [IbVglm](#)
 ... further arguments passed to summary.merMod of **VGAM**

SummaryIbBetareg-class

An S4 class union for summary

Description

Members of the union are [SummaryIbBetareg](#), [SummaryIbGlm](#), [SummaryIbLm](#), [SummaryIbLmer](#), [SummaryIbNegbin](#), [SummaryIbNls](#), [SummaryIbVglm](#) iterative bootstrap procedure

Details

The ‘Functions’ section describes members of the class union.

Functions

- [SummaryIbBetareg-class](#): summary of class `summary.betareg` from **betareg**
- [SummaryIbGlm-class](#): summary of class `summary.glm` from **stats**
- [SummaryIbLm-class](#): summary of class `summary.lm` from **stats**
- [SummaryIbLmer-class](#): summary of class `summary.merMod` from **lme4**
- [SummaryIbNegbin-class](#): summary of class `summary.negbin` from **MASS**
- [SummaryIbNls-class](#): summary of class `summary.nls` from **stats**
- [SummaryIbVglm-class](#): summary of class `summary.vglm` from **VGAM**

Author(s)

Samuel Orso

vcov,Ib-method	<i>Method for calculating covariance matrix from an object in class union "Ib"</i>
----------------	--

Description

Method for calculating covariance matrix from an object in class union "Ib"

Usage

```
## S4 method for signature 'Ib'  
vcov(object, ...)
```

Arguments

object	an object of class union "Ib"
...	further arguments to pass to vcov

See Also

[Ib](#), [vcov](#)

Index

- betareg, [8](#), [9](#)
- bootstrap, [2](#)
- coef, [3](#), [5](#)
- coef, Ib-method, [3](#)
- coefficients, [8](#)
- effects, [4](#)
- effects, Ib-method, [4](#)
- fitted, Ib-method, [4](#)
- fitted.values, [4](#)
- Gamma, [8](#)
- getEst, [5](#)
- getEst, Ib-method (getEst), [5](#)
- getExtra, [5](#), [5](#), [6](#), [12](#)
- getExtra, Ib-method (getExtra), [5](#)
- getIteration, [6](#)
- getIteration, Ib-method (getIteration), [6](#)
- getObject, [7](#), [12](#)
- getObject, Ib-method (getObject), [7](#)
- glm, [8](#), [9](#)
- glm.nb, [8](#), [9](#), [11](#)
- Ib, [3–7](#), [9](#), [15](#), [16](#), [25](#)
- ib, [3](#), [7](#), [11](#), [13](#), [14](#)
- ib, betareg-method (ib), [7](#)
- ib, glm-method (ib), [7](#)
- ib, lm-method (ib), [7](#)
- ib, lmerMod-method (ib), [7](#)
- ib, negbin-method, [11](#)
- ib, nls-method (ib), [7](#)
- ib, vglm-method (ib), [7](#)
- Ib-class (IbBetareg-class), [12](#)
- IbBetareg, [12](#), [17](#), [18](#), [21](#)
- IbBetareg-class, [12](#)
- ibControl, [3](#), [8](#), [11](#), [13](#), [18–20](#)
- IbGlm, [12](#), [18](#), [21](#)
- IbGlm-class (IbBetareg-class), [12](#)
- IbLm, [12](#), [18](#), [19](#), [22](#)
- IbLm-class (IbBetareg-class), [12](#)
- IbLmer, [12](#), [19](#), [22](#)
- IbLmer-class (IbBetareg-class), [12](#)
- IbNegbin, [12](#), [19](#), [23](#)
- IbNegbin-class (IbBetareg-class), [12](#)
- IbNls, [12](#), [20](#), [23](#)
- IbNls-class (IbBetareg-class), [12](#)
- IbVglm, [12](#), [20](#), [24](#)
- IbVglm-class (IbBetareg-class), [12](#)
- inverse.gaussian, [8](#)
- lm, [8](#), [9](#)
- lmer, [8](#), [9](#)
- nls, [9](#)
- plot, Ib, ANY-method, [14](#)
- plot.lm, [15](#)
- predict, [15](#)
- predict, Ib-method, [15](#)
- quasi, [8](#)
- Random, [13](#)
- residuals, [15](#)
- residuals, Ib-method, [15](#)
- show, Ib-method, [16](#)
- show, SummaryIb-method, [16](#)
- simulate, [8](#)
- simulate.vlm, [9](#)
- simulation, [17](#)
- simulation, betareg-method, [17](#)
- simulation, glm-method, [18](#)
- simulation, Ib-method (simulation), [17](#)
- simulation, lm-method, [18](#)
- simulation, lmerMod-method, [19](#)
- simulation, negbin-method, [19](#)
- simulation, nls-method, [20](#)
- simulation, vglm-method, [20](#)
- summary, IbBetareg-method, [21](#)

- summary, IbGlm-method, [21](#)
- summary, IbLm-method, [22](#)
- summary, IbLmer-method, [22](#)
- summary, IbNegbin-method, [23](#)
- summary, IbNls-method, [23](#)
- summary, IbVglm-method, [24](#)
- summary.betareg, [21](#)
- summary.glm, [21](#)
- summary.lm, [22](#)
- summary.negbin, [23](#)
- SummaryIb, [16](#)
- SummaryIb-class
 - (SummaryIbBetareg-class), [24](#)
- SummaryIbBetareg, [24](#)
- SummaryIbBetareg-class, [24](#)
- SummaryIbGlm, [24](#)
- SummaryIbGlm-class
 - (SummaryIbBetareg-class), [24](#)
- SummaryIbLm, [24](#)
- SummaryIbLm-class
 - (SummaryIbBetareg-class), [24](#)
- SummaryIbLmer, [24](#)
- SummaryIbLmer-class
 - (SummaryIbBetareg-class), [24](#)
- SummaryIbNegbin, [24](#)
- SummaryIbNegbin-class
 - (SummaryIbBetareg-class), [24](#)
- SummaryIbNls, [24](#)
- SummaryIbNls-class
 - (SummaryIbBetareg-class), [24](#)
- SummaryIbVglm, [24](#)
- SummaryIbVglm-class
 - (SummaryIbBetareg-class), [24](#)

- vcov, [25](#)
- vcov, Ib-method, [25](#)
- vglm, [9](#)